

In order to provide more accurate inventory information, please select your shipping country.

Select Your Country/Region: European Union



SUBMIT



Red and IR Alignment Laser Diode

Stock #19-447 3-4 DAYS



1



€199,00

ADD TO CART

Qty 1-9

€199,00

Qty 10+

€179,10

Volume Pricing

[Request Quote](#)

⚠ Prices shown are exclusive of VAT/local taxes

Get Product Downloads



Operating Temperature (°C):  
-10 to 50

Operating Voltage (V):  
5

Output Power (mW):  
25

|                                                                                                                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Wavelength (nm):</b><br>780.00                                                                                                                                                                                                           |
| <b>Wavelength Tolerance (nm):</b><br>±5                                                                                                                                                                                                     |
| <b>Power Supply:</b><br>Power Supply Required and Sold Separately.<br>USA: <a href="#">#83-855</a><br>Europe: <a href="#">#83-855</a><br>Japan: <a href="#">#13-640</a><br>Korea: <a href="#">#33-770</a><br>China: <a href="#">#83-855</a> |
| <b>Modulation Frequency (kHz):</b><br>0 - 10                                                                                                                                                                                                |
| <b>Beam Diameter (mm):</b><br>3.5 typical                                                                                                                                                                                                   |
| <b>Beam Divergence (mrad):</b><br><1.0                                                                                                                                                                                                      |
| <b>Laser Class - CDRH:</b><br>IIIb                                                                                                                                                                                                          |
| <b>Color:</b><br>infrared                                                                                                                                                                                                                   |
| <b>Length (mm):</b><br>36.00                                                                                                                                                                                                                |

### Regulatory Compliance

|                                                            |
|------------------------------------------------------------|
| <b>RoHS 2015:</b><br><a href="#">Compliant</a>             |
| <b>Certificate of Conformance:</b><br><a href="#">View</a> |
| <b>Reach 233:</b><br><a href="#">Compliant</a>             |

---