NOTES:

1. SUBSTRATE MATERIAL: N-BK7


2. COATING (APPLY ACROSS CLEAR APERTURE)


S1 & S2: MgF2

R(avg) ≤1.75% @ 400 - 700nm



- 4. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICAIONS APPLY ACROSS CLEAR APERTURE
- 5. Rohs Compliant





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	S1	S2					
SHAPE	CONVEX	PLANO	EFL	50		Edmund Ontion	○ ®
RADIUS	25.84	∞	BFL	48.68		Edmund Optics	S
SURFACE QUALITY	60-40	60-40				10mm DIA X 50mm FL MgF2 COATED)
CLEAR APERTURE	Ø9.00	Ø9.00	THIRD ANGLE PROJECTION		TITLE	CYLINDER LENS	
COATING APERTURE	Ø9.00	Ø9.00					
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	47770	SHEET 1 OF 1