

NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(AVG) ≤1.75% @ 400 - 700nm



5. Rohs Compliant







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

| | \$1 | \$2 |
|-----------------|----------------------|----------------------|
| SHAPE | PLANO | PLANO |
| SURFACE QUALITY | 60-40 | 60-40 |
| CLEAR APERTURE | Ø22.50 | Ø22.50 |
| BEVEL | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED |

| THIRD ANGLE PROJECTION | $\phi \Leftrightarrow$ | TITLE |
|------------------------|------------------------|--------|
| ALL DIMS IN | mm | DWG NO |

| 25mm DIA., 2mm THICK, MgF2 COATED λ/4 N- |
|--|
| BK7 WINDOW |

Edmund Optics

SIN mm DWG NO 36998 SHEET 1 OF 1