


NOTES:


- 1. SUBSTRATE: CRYSTAL QUARTZ
- 2. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 405nm DAMAGE THRESHOLD: 3.5 J/cm² @10ns @ 1064nm
- 3. SURFACE S1 TO BE PARALLEL TO SURFACE S2 TO WITHIN <0.5 arcsec
- 4. RETARDANCE: $\lambda/4 \pm \lambda/200$
- 5. TRANSMITTED WAVEFRONT: λ/10 FOR CENTRAL 80% OF CLEAR APERTURE
- 6. Rohs Compliant





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING





SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	THIRD ANGLE PROJECTION		TITLE	Ø25.4mm, 405nm, λ/4 QUARTZ WAVEPLA ZERO ORDER	
CLEAR APERTURE	Ø15.0	Ø15.0		· ·			CLIEFT
SURFACE QUALITY	10-5	10-5	ALL DIMS IN	mm	DWG NO	83927	SHEET 1 OF 1