NOTES:

1. SUBSTRATE: B270


2. COATING (APPLY ACROSS COATING APERTURE)


S1 &S2: UNCOATED

3. CONSTRUCTION: DICHROIC

4. THE POLARIZER CONSISTS OF A POLYMER POLARIZATION FILM CEMENTED BETWEEN TWO PIECES OF OPTICAL GLASS

5. ROHS: COMPLIANT





FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

				ĺ
REV. A	VALUE		1	Γ
WAVELENGTH RANGE (nm)	1000 - 2000	THIRD ANGLE PROJECTION	$\bigoplus \bigoplus$	
EXTINCTION RATIO	>1000:1		ı	
TRANSMISSION	33%	ALL DIMS IN	mm	

		Edmund Optics®
IGLE TON	TITLE	Ø25mm, 1000-2000nm, NIR LINEAR POLARIZE

THIRD ANGLE _ PROJECTION	\bigcirc	TITLE	Ø25mm, 1000-2000nm, NIR LINEAR PO	LARIZER
	ı			
ALL DIMS IN	mm	DWG NO	48888	SHEET