1. SUBSTRATE: N-F2

2. COATING:

S1 & S2: NONE


3. FOCAL LENGTH TOLERANCE: ±5%


4. CENTERING: 25 ARCMIN

5. RoHS: COMPLIANT

6. ASPHERIC SURFACE DESCRIBED BY THE FOLLOWING EQUATION AND COEFFICIENTS SHOWN IN TABLE BELOW

$$Z_{ASPH}(Y) = \frac{(\sqrt{1/RADIUS})^* Y^2}{1 + \sqrt{1 - (1 + k)^* (\sqrt{1/RADIUS})^2 * Y^2}} + D * Y^2 + E * Y^4 + F * Y^6 + G * Y^8 + H * Y^{10} + J * Y^{12} + L * Y^{10} + J * Y^{10}$$





ALL DIMS IN

COEFFICIENT TABLE		
COEFFIECIENT	\$1	
SEMI-DIAMETER	8.000000E+00	
(1/RADIUS)	0.146941E+00	
k	-1.00000E+00	
D	0.000000E+00	
Е	1.764200E-04	
F	1.327300E-06	
G	-5.529600E-09	
Н	0.000000E+00	
J	0.000000E+00	
L	0.000000E+00	

SHEET

1 OF 1

## SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2	
SHAPE	CONVEX	PLANO	
SURFACE QUALITY	As Molded	As Molded	
CLEAR APERTURE	Ø12.80	Ø12.80	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	

EFL: 10.8mm	P	Edmund Optics®
BFL: 5.86mm		
THIRD ANGLE PROJECTION	TITLE	16mm DIA. X 10.8mm FL, UNCOATED MOLDED ASPHERIC CONDENSER LENS

34459

DWG NO