
## NOTES:


- 1. SUBSTRATE:
  IR GRADE FUSED SILICA
- 2. COATING (APPLY ACROSS COATING APERTURE) S1 & S2: NONE
- 3. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN ≤ 30 ARCSEC

4. FINE GRIND SURFACE

5. WAVELENGTH RANGE: 200 - 3500nm

6. TRANSMITTED WAVEFRONT DISTORTION P-V: ≤1/6 WAVE





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	20-10	20-10
CLEAR APERTURE	90 %	90 %
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	$\phi$	TITLE
ALL DIMS IN	mm	DWG

	Edmund Optics®
TITLE	25.4mm Dia., Uncoated, IR Ultrafast Thin Window

	1		· · · · · · · · · · · · · · · · · · ·	
ll dims in	mm	DWG NO	11753	SHEET 1 OF 1