
## NOTES:


1. SUBSTRATE:


Lithium Fluoride (LiF)

- 2. SURFACE \$1 TO BE PARALLEL WITH SURFACE \$2 TO WITHIN <3 arcmin
- 3. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: NONE







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
SURFACE FLATNESS	λ/2 @ 633nm	λ/2 @ 633nm
CLEAR APERTURE	Ø 22.5	Ø 22.5
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED

			U
		1	
	THIRD ANGLE PROJECTION	$\bigcirc$	T
		l	
)	ALL DIMS IN	mm	С

Edmund	Optics®

25mm Dia., 2mm Thick, Uncoated, Lithiur	η
Fluoride (LiF) Window	

IN	mm	DWG NO	19728	SHEET 1 OF 1
----	----	--------	-------	-----------------