


12.5mm Dia. x 50mm FL, Uncoated, Best Form Spherical Lens



Best Form Spherical Lenses



Stock **#22-566** 13 In Stock

-

1

+

€166^{.86}

ADD TO CART

Volume Pricing	
Qty 1-9	€166,86 each
Qty 10-25	€150,38 each
Qty 26-49	€133,90 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

SPECIFICATIONS

General

Double-Convex Lens		Type:
Physical & Mechanical Properties		
12.50 +0/-0.025	Diameter (mm):	
<1	Centering (arcmin):	
Protective as needed	Bevel:	
2.10 ±0.05	Center Thickness CT (mm):	
1.24	Edge Thickness ET (mm):	
11.25	Clear Aperture CA (mm):	
Optical Properties		
48.81	Back Focal Length BFL (mm):	
50.00	Effective Focal Length EFL (mm):	
Uncoated	Coating:	
Fused Silica	Substrate: ☐	
10-5	Surface Quality:	
1.5λ	Power (P-V) @ 632.8nm:	
λ/4	Irregularity (P-V) @ 632.8nm:	
125.00	Radius R ₁ (mm):	
27.92	Radius R ₂ (mm):	
4	f/#:	
587.6	Focal Length Specification Wavelength (nm):	
0.13	Numerical Aperture NA:	
200 - 2200	Wavelength Range (nm):	
Infinite	Conjugate Distance:	
Regulatory Compliance		
View	Certificate of Conformance:	

PRODUCT DETAILS

- Asymmetrical Design for Precise Focusing and Small Spot Size
- Uncoated Fused Silica Substrate with 10-5 Surface Quality
- Ideal for Higher Power Laser Applications

Best Form Spherical Lenses are double-convex (DCX) lenses designed with asymmetrical faces to achieve the smallest possible spot size with spherical surfaces. Featuring 10-5 surface quality and utilizing UV Fused Silica substrates, these lenses are an alternative to laser grade aspheric lenses. With common diameters and various focal lengths available, these lenses can easily be integrated into optical systems requiring precise focusing. Best Form Spherical Lenses are optimized to reduce spherical aberration and far exceed performance of plano-convex (PCX) lenses without the cost associated with aspheric lens designs. These lenses are ideal for precise laser applications where the large aperture diffraction limited performance of an aspheric lens is not needed.