

TECHSPEC[®] 25.4mm Dia., 532nm T, 1064nm R 45° Harmonic Separator



TECHSPEC Nd:YAG Harmonic Separators

Stock **#37-698** 20+ In Stock

-

1

+

€302⁰⁰

ADD TO CART

Volume Pricing	
Qty 1-5	€302,00 each
Qty 6-24	€272,00 each
Qty 25-49	€242,00 each
Need More?	Request Quote

i Prices shown are exclusive of VAT/local taxes

Product Downloads

General

Harmonic Beamsplitter

Type:

Physical & Mechanical Properties

>85

Clear Aperture (%):

Construction:

Dichroic	
	Diameter (mm):
25.40 +0.00/-0.10	
	Parallelism (arcmin):
<3	
	Thickness (mm):
6.35 ±0.20	

Optical Properties	
	Angle of Incidence (°):
45	
	Coating Specification:
Surface 1: R _{abs} : >99% @ 1064nm, T _{abs} : >95% @ 532nm	
Surface 2: R _{abs} : <0.5% @ 532nm	
	Reflection Wavelength (nm):
1064	
	Substrate: ☐
Fused Silica (Corning 7980)	
	Surface Flatness (P-V):
λ/10	
	Surface Quality:
10-5	
	Transmission Wavelength (nm):
532	
	Damage Threshold, By Design: ☐
Surface 1:	
7.5 J/cm² @ 1064nm, 20ns, 20Hz	
7.5 J/cm² @ 532nm, 20ns, 20Hz	
Surface 2:	
10 J/cm² @ 532nm, 20ns, 20Hz	

Regulatory Compliance	
	RoHS 2015:
Compliant	
	Reach 209:
Compliant	
	Certificate of Conformance:
View	

Product Details

- Used to Separate Nd:YAG Harmonic Wavelengths
- Beamsplitter Coating Features >95% Transmission
- λ/10 Fused Silica Substrate

TECHSPEC® Nd:YAG Harmonic Separators are used to separate the common harmonic wavelengths of an Nd:YAG laser. A beamsplitter coating on the first surface reflects at least one wavelength and transmits another. The second surface of the beamsplitter features an anti-reflective coating to minimize the loss due to reflection. TECHSPEC Nd:YAG Harmonic Separators are available in 45° and 0° angle of incidence options. These harmonic separators are available in multiple wavelength configurations for optimal flexibility in system design.

Note: The Damage Threshold values we publish for this family of products were all tested independently from one another. When using these products with more than 1 incident beam, the resulting Damage Threshold of the system will be negatively impacted.

Compatible Mounts