See all 68 Products in Family

TECHSPEC® 2mm Aperture, 75mm L Low NA, Hexagonal Light Pipe



N-BK7 Light Pipe Homogenizing Rods

Stock **#63-081** **20+ In Stock**

- 1 + **€207**.00

ADD TO CART

Volume Pricing	
Qty 1-5	**€207,00** each
Qty 6-25	**€166,00** each
Qty 26-49	**€156,00** each
Need More?	Request Quote

Prices shown are exclusive of VAT/local taxes

Product Downloads

General

Type:

Light Pipe

Physical & Mechanical Properties

Length (mm):	75.00
Parallelism (arcmin):	<5.00
Length Tolerance (mm):	±0.3
Light Source NA:	Low

Optical Properties

Coating:	Uncoated
Substrate:	N-BK7
Surface Quality:	60-40
Entrance and Exit Aperture (mm):	2.00
Aperture Tolerance (mm):	±0.10
Image Orientation:	Light Homogenization
Wavelength Range (nm):	350 - 2200
Surface Flatness (P-V):	1λ

Regulatory Compliance

RoHS 2015:	Compliant
Reach 209:	Compliant
Certificate of Conformance:	View

Need different specs or modifications?

Edmund Optics offers comprehensive custom manufacturing services for optical and imaging components tailored to your specific application requirements. Whether in the prototyping phase or preparing for full-scale production, we provide flexible solutions to meet your needs. Our experienced engineers are here to assist—from concept to completion.

Our capabilities include:

- Custom dimensions, materials, coatings, and more
- High-precision surface quality and flatness
- Tight tolerances and complex geometries
- Scalable production—from prototype to volume

Learn more about our custom manufacturing capabilities or submit an inquiry here.

Product Details

- Homogenizes Non-Uniform Light Sources
- Hexagonal Entrance Aperture
- Uncoated and VIS-EXT Coated Options Available
- Ideal for OEM Illumination
- Additional **Light Pipe Homogenizing Rods** Available

TECHSPEC® N-BK7 Light Pipe Homogenizing Rods utilize total internal reflection to homogenize non-uniform light sources regardless of spectral characteristics. Their hexagonal configurations provide 35% less light loss than a comparable square configuration. Low Numerical Aperture (NA) sources require longer pipes to uniformly homogenize light, while shorter pipes will sufficiently homogenize the output from high NA sources. TECHSPEC N-BK7 Light Pipe Homogenizing Rods are made from precision N-BK7 for use in a variety of visible light applications and are available uncoated or with VIS-EXT coatings.

Fused silica versions of our light pipe homogenizing rods are also available. **TECHSPEC® Light Pipe Homogenizing Rod Mounts**, specifically designed to hold our standard and fused silica families of light pipe homogenizing rods, are available; these mounts greatly simplify the handling and integration of these components.

Technical Information



;