

## 38.4mm Diameter x 30mm FL, PCX Condenser Lens



Stock **#43-594** **15 In Stock**

[Other Coating Options](#)

€52.<sup>00</sup>

**ADD TO CART**

### Volume Pricing

Qty 1-10	€52,00 each
Qty 11-49	€46,00 each
Need More?	<a href="#">Request Quote</a>

**!** Prices shown are exclusive of VAT/local taxes

### Product Downloads

### General

Condenser Lens **Type:**

### Physical & Mechanical Properties

38.40 +0.2/-0.4 **Diameter (mm):**

≤25 **Centering (arcmin):**

Center Thickness CT (mm):  
19.00 ±0.25

Bevel:  
Protective as needed

Shape of Back Surface:  
Convex

## Optical Properties

Effective Focal Length EFL (mm):  
30.00

Numerical Aperture NA:  
0.64

Substrate:   
**B270**

Focal Length Tolerance (%):  
±7

Coating:  
Uncoated

Surface Quality:  
80-50 (typical)

f#:  
0.78

Abbe Number ( $v_d$ ):  
58.5

Index of Refraction ( $n_d$ ):  
1.523

Radius  $R_2$  (mm):  
84.125

Wavelength Range (nm):  
350 - 2500

Conjugate Distance:  
Infinite

## Material Properties

Coefficient of Thermal Expansion CTE ( $10^{-6}/^{\circ}\text{C}$ ):  
9.4

## Regulatory Compliance

RoHS 2015:  
**Compliant**

Certificate of Conformance:  
[View](#)

## Product Details

- Molded Illumination Lenses
- Aspheric or Spherical Designs
- High Numerical Apertures

Condenser Lenses are molded lenses designed for illumination applications. Featuring large apertures and short focal lengths, Condenser Lenses are commonly used in emitter-detector applications, projection applications, or condensing illumination applications such as Koehler Illumination. The Aspheric Condenser Lenses are molded on the aspheric surface and ground and polished on the opposite face, offering superior performance. The Plano-Convex (PCX) Condenser Lenses are molded on both surfaces, offering excellent value.

## Technical Information



