Edmund

In order to provide more accurate inventory information, please select your shipping country:

Select Your Country/Region: European Union

SUBMIT

50µm 0.22 NA UV/VIS Fiber, 25m Length

Stock **#57-072** 3-4 DAYS

- 1 + **€145,00**

ADD TO CART

Qty 1-4
€145,00

Qty 5+
€128,00

Volume Pricing
Request Quote

Prices shown are exclusive of VAT/local taxes

Get Product Downloads

Acceptance Angle (°):
25.4

Buffer Material:
Polyimide

Cladding Diameter (µm):

125 +1/-3

Coating:
UV/VIS

Minimum Bend Radius (mm):
25/13 (Continuous/Momentary)

Substrate:
Fused Silica (Corning 7980)

Length (m):
25.00

Numerical Aperture NA:
0.22

Operating Temperature (°C):
-190 to +390

Outer Diameter (µm):
145 ±5

Core Diameter (µm):
50 ±2

Index of Refraction n_d - Core:
1.457

Index of Refraction n_d - Cladding:
1.439

Wavelength Range (nm):
190 - 1250

Numerical Aperture (NA) Tolerance:
±0.02

Regulatory Compliance

RoHS 2015:
Compliant

Reach 209:
Compliant

Certificate of Conformance:
View