


[See all 7 Products in Family](#)

# 50X Mitutoyo Telecentric Objective

See More by [Mitutoyo](#)



3X (#56-985) & 5X (#56-986)



Stock #87-229 [CONTACT US](#)

- 1 + €4.390<sup>00</sup>

**ADD TO CART**

Volume Pricing	
Qty 1+	€4.390,00 each
Need More?	<a href="#">Request Quote</a>

**i** Prices shown are exclusive of VAT/local taxes

## Product Downloads

### General

375-052 **Model Number:**

Microscope Objective **Type:**

Finite Conjugate **Style:**

Mitutoyo **Manufacturer:**

**Note:**  
Image is formed 280mm from specimen (170mm from the mounting flange)

## Physical & Mechanical Properties

97.00 **Length (mm):**

97.00 **Length excluding Threads (mm):**

39 **Maximum Diameter (mm):**

350 **Weight (g):**

## Optical Properties

0.13mm **Horizontal Field of View, 1/2" Sensor:**

0.18mm **Horizontal Field of View, 2/3" Sensor:**

3.61 **Focal Length FL (mm):**

NA0.55 **Aperture (f#):**

50X **Magnification:**

0.55 **Numerical Aperture NA:**

0.5 **Resolving Power ( $\mu\text{m}$ ):**

0.90 **Depth of Field ( $\mu\text{m}$ ):**

0.36 **Field of View, 18 Diameter Field Eyepiece (mm):**

0.45 **Field of View, 24 Diameter Field Eyepiece (mm):**

13 **Working Distance (mm):**

435 - 655 **Wavelength Range (nm):**

110 **Parfocal Length (mm):**

N/A **Immersion Liquid:**

11.00 **Maximum Image Circle (mm):**

## Sensor

2/3" **Maximum Sensor Format:**

## Threading & Mounting

M26 x 36 TPI **Mount:**

M26 x 36 TPI **Mounting Threads:**

## Environmental & Durability Factors

+5 to +40 **Operating Temperature ( $^{\circ}\text{C}$ ):**

20 - 80% **Operating Humidity:**

## Regulatory Compliance

**Exempt** **RoHS 2015:**

**View** **Certificate of Conformance:**

**Contains SVHC(s)** **REACH 241:**

## Product Details

- Long Working Distances Allow for Integration into Machine Vision Measurement Systems
- Compact Design and Long Parfocal Length Simplifies Mounting
- [Tube](#) Available for Use with C-Mount Cameras
- Aluminum Alloy Housing

Mtutoyo Telecentric Objectives are ideal for high-resolution, high power machine vision measurement and optical gauging systems. With powers up to 100X, these objectives can be used for semiconductor production and inspection, and in metrology, quality assurance, and R&D laboratories. These objectives are constructed of an aluminum alloy housing. Mtutoyo Telecentric Objectives have a compact design and a long parfocal length that simplifies mounting. They are easily integrated into C-Mount imaging systems with our Mtutoyo C-Mount Camera Tube [#56-992](#).

Edmund Optics is the main source for Mtutoyo Objectives. Place your orders now for these in demand quality products.

## Technical Information

Magnification	A	B	C	D	E	Stock No.
1X	49	10	16.5	31.5	31.5	<a href="#">#56-984</a>
3X	33	10	18	25	28	<a href="#">#56-985</a>
5X	49	10	17	25	28	<a href="#">#56-986</a>
10X	59	10	14.5	30	30	<a href="#">#56-987</a>
20X	90	14.5	23	33	39	<a href="#">#87-228</a>
50X	97	14.7	23	33	39	<a href="#">#87-229</a>
100X	104	14.1	23	33	39	<a href="#">#87-230</a>