

510mm, 355nm JENar™ Silverline™ F-Theta Scanning Lens

See More by [Jenoptik](#)



Stock **#17-026** **4 In Stock**

-

1

+

€4.367²⁰

ADD TO CART

Volume Pricing	
Qty 1+	€4.367,20 each
Need More?	Request Quote

i Prices shown are exclusive of VAT/local taxes

Product Downloads

SPECIFICATIONS

General

017700-405-26

Model Number:

JENar Silverline F-Theta

Type:

Note: Damage Warning: Not recommended for picosecond and femtosecond laser pulses.	
Protective Window: #17-695: One Included	
Manufacturer: Jenoptik	
Physical & Mechanical Properties	
Maximum Diameter (mm):	104.8 +0/-0.2
Weight (g):	700
X/Y Mirror Angle (°):	±9.2
Flange Distance (mm):	637
Input Beam Diameter, 1/e ² (mm):	14
Maximum Length (mm):	54.3
Optical Properties	
Focal Length FL (mm):	510.00
Substrate:	Fused Silica (Corning 7980)
Scan Angle (°):	±25.7
Scan Field (mm):	328 x 328
Telecentricity (°):	F-Theta Only: 18.20 With Scanner: 18.20
Working Distance (mm):	609
Wavelength Range (nm):	355
Damage Threshold, By Design:	1.0 J/cm ² * (τ/[ns]) ^{0.40} 1.0 MW/cm ²
Scan Field Diameter (mm):	431
Focus Size Diameter, 1/e ² (μm):	24
GDD Specification (fs ²):	5260
Damage Threshold, Pulsed:	1.0 J/cm ² * (τ/[ns]) ^{0.40}
Damage Threshold, CW:	1.0 MW/cm ²
Threading & Mounting	
Mounting Threads:	M85 x 1
Regulatory Compliance	
Certificate of Conformance:	View

PRODUCT DETAILS

- Low-Absorption Fused Silica Substrates for High-Power Laser Applications
 - Large Scan Fields Up to 328mm x 328mm
 - High Damage Thresholds and Low Telecentricity Errors
 - Jenoptik JENar™ F-Theta Scanning Lenses Also Available
- Jenoptik JENar™ Silverline™ F-Theta Scanning Lenses provide flat field at the image plane and feature low-absorption fused silica substrates, making them suitable for high-power laser applications. These F-Theta lenses offer high damage thresholds to handle beam powers of up to four kilowatts without active cooling and are available in various wavelengths ranging from 266nm to 1100nm. With large processing areas up to 328mm x 328mm, low telecentricity errors, and diffraction-limited image quality, these lenses allow for high spot consistency and increased throughput over the entire scanning range. With their patented stackable mounting technology, these lenses compensate for thermal stresses and improve the stability of the optical components, ensuring high-precision adjustment and position control in OEM systems. Jenoptik JENar™ Silverline™ F-Theta Scanning Lenses were specially developed for applications requiring high-power and short-pulse Nd:YAG, Yb:doped, and fiber laser sources and are used in conjunction with [galvanometers](#) and [beam expanders](#).
- Contact us if your application requires [Jenoptik JENar™ F-Theta Scanning Lenses](#) or Jenoptik JENar™ Silverline™ F-Theta Scanning Lenses not shown on our website.