

632.8nm Free Space Frequency Stabilized Laser Diode



632.8nm Frequency Stabilized Laser Diodes (Free Space and Fiber-Coupled options shown)

Stock **#33-045** 1 In Stock

-

1

+

€6.860⁰⁰

ADD TO CART

Volume Pricing	
Qty 1-5	€6.860,00 each
Qty 6+	€6.170,00 each
Need More?	Request Quote

Prices shown are exclusive of VAT/local taxes

Product Downloads



SPECIFICATIONS

General

2.00

Warm-Up Time (minutes):

1.5 - 2 (Output Beam)

Aspect Ratio:

Diode	Type of Laser:
IIIb	Laser Class - CDRH:
Physical & Mechanical Properties	
71.0 L x 63.5 W x 19.8 H	Dimensions (mm):
135.00	Weight (g):
<50 (8 Hours)	Pointing Stability (µrad):
Optical Properties	
100:1 Linear	Polarization:
632.80	Wavelength (nm):
1.1 (Horizontal) 1.2 (Vertical)	Mode Quality, M²:
±0.5	Wavelength Tolerance (nm):
0.8 x 1.6	Beam Diameter (mm):
Typical: 10	Spectral Line Width (MHz):
±0.002	Beam Stability (nm):
1.3 x 0.8	Beam Divergence (mrad):
Red	Color:
Electrical	
55	Output Power (mW):
1.00	Power Stability (%):
Max 5	Power Consumption (W):
±10	Output Power Tolerance (%):
10 Hz - 100 MHz 0.2% RMS	Noise Level:
Max 2 @ 3.3 V	Input Current (A):
Hardware & Interface Connectivity	
10-pin Connectors (cable provided upon request)	Electrical Leads/ Pin Connections:
USB	Computer Interface:
Free Space	Output Type:
Environmental & Durability Factors	
+15 to +40	Operating Temperature (°C):
5 - 95% (non-condensing)	Operating Humidity:
Regulatory Compliance	
View	Certificate of Conformance:

PRODUCT DETAILS

- Single Longitudinal Mode (SLM) Performance
- ±0.002nm Wavelength Stability
- Very Low Power Consumption

632.8nm Frequency Stabilized Laser Diodes are ideal for typical HeNe laser applications including flow cytometry, interferometry, confocal microscopy, fluorescence excitation, and Raman spectroscopy. Whereas a comparable HeNe laser would be larger, more expensive, and consume more power, the 632.8nm Frequency Stabilized Laser Diodes feature more compact designs, ±0.002nm wavelength stability, and either greater than 60mW power (free-space model) or greater than 20mW power (fiber coupled model). Additionally, these lasers utilize Variable Bragg Gratings (VBG) to lock the 632.8nm wavelength to a 10MHz linewidth.

