

[All Products](#) / [Optics](#) / [Optical Filters](#) / [M25.5 and M30.5 Mounted Neutral Density Filters](#)

[See all 52 Products in Family](#)

TECHSPEC® 700-1200nm



Please select your shipping country to view the most accurate inventory information, and to determine the correct Edmund Optics sales office for your order.

Select Your Country/Region: European Union

Submit

1

€161⁰⁰

ADD TO CART

| Volume Pricing | |
|----------------|-------------------------------|
| Qty 1-9 | €161,00 each |
| Qty 10-25 | €144,00 each |
| Need More? | Request Quote |

Prices shown are exclusive of VAT/local taxes

Product Downloads

- STEP:step
- Curve:pdf
- PDF Drawing:pdf
- IGES:igs
- eDrawing:eprt
- EO Spec Sheet
- [Download All](#)

General

Type: Neutral Density Filter

Stock No. of Unmounted Filter: #63-411

Physical & Mechanical Properties

Diameter (mm): 28.00

Clear Aperture CA (mm): 22.0

Optical Properties

Optical Density OD (Average): 1.3

Substrate: B270

Coating: Non-Reflective ND

Transmission (%): 5.00

Wavelength Range (nm): 700 - 1200

Threading & Mounting

Filter Thread: M25.5 x 0.50

Mount Thickness (mm): 9.9

Regulatory Compliance

Certificate of Conformance: [View](#)

Product Details

- VIS and NIR ND Filters, Mounted for Imaging Lenses
- Variety of Optical Densities
- Stack Filters Together for Custom Transmission Profiles

Our **TECHSPEC® Absorptive Neutral Density Filters** and **TECHSPEC® NIR Non-Reflective Neutral Density Filters** are now available in M25.5 and M30.5 mounts for imaging lenses. Neutral Density (ND) filters are useful for limiting the amount of light that reaches the sensor of a camera. Using ND filters rather than the iris of your lens allows the imaging system to limit the depth of field of the image, eliminating parallax errors and other image artifacts that may limit the usefulness of your machine vision software.

We have specially designed our mounts to hold filters up to 6.5mm in thickness, allowing the user to stack multiple ND filters together to create custom transmission filters. Optical Densities are additive, meaning a filter stack of a 0.4 OD filter and a 1.3 OD filter will produce a 1.7 Optical Density.

Please select your shipping country to view the most accurate inventory information, and to determine the correct Edmund Optics sales office for your order.

Select Your Country/Region:

Accessories

Note: Compatible accessories for individual stock numbers may vary. If unsure about which accessories work with your products, please contact us [here](#).

| | Title | Compare | Stock Number | Price | Buy |
|-----------------------|---|---------|--------------|--|---|
| MORE+ | M25.5 x 0.5 Mount for 25mm Diameter Filters | | #65-800 | €60,00 Volume Pricing Request Quote | 20+ In Stock <input type="text" value="1"/> |
| MORE+ | M30.5 x 0.5 Mount for 25mm Diameter Filters | | #65-801 | €59,00 Volume Pricing Request Quote | 8 In Stock <input type="text" value="1"/> |

Resources

Media Type

- Application Note
- FAQ
- Glossary
- Video
- Published Article
- Technical Tool

APPLICATION NOTE

Understanding Neutral Density Filters

? FAQ

What is an ND Filter?

? FAQ

Can I place ND filters back-to-back and increase...

? FAQ

What is the difference between using an absorptiv...

? FAQ

How should I orient my reflective ND or interferenc...

GLOSSARY

Continuously Variable Apodizing Filter

[View More](#)