

[See all 15 Products in Family](#)

Coherent® EnergyMax 1191437 | Nd:YAG Sensor, 2.4mJ-3J, USB

See More by [Coherent®](#)



Coherent® EnergyMax Laser Energy Sensors

Stock #88-421 [CONTACT US](#)

- 1 + €3.200⁰⁰

ADD TO CART

Volume Pricing	
Qty 1+	€3.200,00 each
Need More?	Request Quote

ⓘ Prices shown are exclusive of VAT/local taxes

Product Downloads

General

Model Number:
J-50MB-YAG
Coherent Part Number: 1191437

Type:
Meterless

Linearity (%):
±3

Calibration Uncertainty (%):
±2

<240	Noise Equivalent Energy (μJ):
	Maximum Incident Energy Density: 14J/cm ² (10ns, 1064nm) 2.8J/cm ² (10ns, 532nm) 0.75J/cm ² (10ns, 355nm) 1.0J/cm ² (10ns, 266nm)
2.4mJ - 3J	Energy Range:
Physical & Mechanical Properties	
35	Active Area Diameter (mm):
Optical Properties	
1064	Calibration Wavelength (nm):
340	Maximum Pulse Width (μs):
266 - 2100	Wavelength Range (nm):
Sensor	
Pyroelectric	Type of Sensor:
Electrical	
50	Maximum Repetition Rate (pps):
20	Maximum Incident Beam Power (W):
Hardware & Interface Connectivity	
USB	Connector:
3.0	Length of Cable (m):
Regulatory Compliance	
Exempt	RoHS 2015:
Contains SVHC(s)	Reach 224:
View	Certificate of Conformance:

Product Details

- ISO 17025 Certified
- Embedded Spectral Compensation Characteristics
- Automatic Temperature Compensation

Coherent® EnergyMax Laser Energy Sensors are designed for a variety of demanding laser measurement applications. These energy sensors, available in meter or meterless USB configurations, incorporate a diffuse coating to minimize specular reflection and feature large active areas. The J-50MB-YAG combines the MaxBlack coating with a diffuser for use with high energy lasers of up to 3J. Coherent® EnergyMax Laser Energy Sensors utilize onboard sensors to automate temperature compensation for improved measurement accuracy.